



| <u>Modelo de apoyo para carro birriel</u> | <u>Carga/Trabajo Tn</u> | <u>Potencia/RPM Aparejo</u> | <u>Potencia carro</u> | <u>Velocidad</u> | <u>Alzada</u> | <u>Tiros</u> | <u>∅ Cable 6*36 alma textil</u> | <u>Peso Kg</u> | <u>Mts Cable</u> |
|---|-------------------------|---------------------------------|---------------------------|------------------|---------------|--------------|---|----------------|----------------------|
| MDE-AB_T5_A6_C11 | 5 | 5,5 Hp/1000 RPM | N/A | 4 m/min | 6 mts | 4 | 11,11 | 250 | 29 |
| MDE-AB_T5_A9_C11 | | | | | 9mts | | | 277 | 41 |
| MDE-AB_T5_A12_C11 | | | | | 12mts | | | 301 | 53 |
| MDE-AB_T5_A15_C11 | | | | | 15mts | | | 323 | 65 |
| MDE-AB_T5_A18_C11 | | | | | 18mts | | | 341 | 79 |
| MDE-AB_T5_A24_C11 | | | | | 24mts | | | 392 | 101 |
| MDE-AB_T5_A30_C11 | | | | | 30mts | | | 465 | 125 |
| | MEDIDAS | | | | | | | | |
| <u>Modelo de apoyo para carro birriel</u> | <u>L</u> | <u>L1</u> | <u>L2</u> | <u>AF</u> | <u>A</u> | <u>LF</u> | <u>H</u> | <u>H1</u> | <u>HC</u> |
| MDE-AB_T5_A6_C11 | 1307 | 441 | 836 | 224 | 584 | 786 | 910 | 509 | N/A |
| MDE-AB_T5_A9_C11 | 1521 | 441 | 1049 | 224 | 584 | 999 | 910 | 509 | |
| MDE-AB_T5_A12_C11 | 1734 | 441 | 1262 | 224 | 584 | 1212 | 910 | 509 | |
| MDE-AB_T5_A15_C11 | 1947 | 441 | 1475 | 224 | 584 | 1425 | 910 | 509 | |
| MDE-AB_T5_A18_C11 | 2160 | 441 | 1688 | 224 | 584 | 1638 | 910 | 509 | |
| MDE-AB_T5_A24_C11 | 2586 | 441 | 2114 | 224 | 584 | 2064 | 910 | 509 | |
| MDE-AB_T5_A30_C11 | 3010 | 441 | 2539 | 224 | 584 | 2485 | 910 | 509 | |